

Part number: 536393
Order code 1: ADN-125-80-A-P-A
Order-ID: C153548

Technical data

Feature name	Value
Stroke	80 mm
Piston diameter	125 mm
Short type code	ADN
Based on standard	ISO 21287
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Design	Piston Piston rod Profile barrel
Position detection	For proximity switch
Variants	Piston rod at one end
Operating pressure (MPa)	0,060...1,000 MPa
Operating pressure (bar)	0,600...10,000 bar
Operating mode	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Note on operating/pilot medium	Lubricated operation possible (required for further use)
Corrosion resistance class KBK	Moderate corrosion stress - 2
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom class	Class 5 as per ISO 14644-1
Ambient temperature	-20...80 °C
Theoretical force at 0.6 MPa (6 bar, 87 psi), retracting	7069 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advancing	7363 N
Product weight	3880 g
Moving mass	1252 g
Type of mounting	Alternatively: With through-hole With internal thread "With accessories" means indirect mounting via an intermediate element.
Pneumatic connection	G1/4
Note on materials	RoHS-compliant
Flange screws material	Steel
Cover material	Die-cast aluminum, coated
Piston rod material	High-alloy steel
Cylinder barrel material	Wrought aluminum alloy, smooth-anodized
Operating pressure (psi)	8,700...145,000 psi