

Technical data

FESTO

 Condition of use

Part number: 536416
Order code 1 : AEN-20-15-I-P-A
Order-ID: C222079

Technical data

Feature name	Value
Stroke	15 mm
Piston diameter	20 mm
Short type code	AEN
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Conforms to standard	ISO 21287
Design	Piston Piston rod Profile barrel
Position detection	For proximity switch
Operating pressure (MPa)	0,100...1,000 MPa
Operating pressure (bar)	1,000...10,000 bar
Operating mode	Single-acting Pushing Pulling
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Note on operating/pilot medium	Lubricated operation possible (required for further use)
Corrosion resistance class KBK	Moderate corrosion stress - 2
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20...80 °C
Theoretical force at 0.6 MPa (6 bar, 87 psi), retracting	105 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advancing	152 N
Moving mass	32 g
Product weight	155 g
Type of mounting	Alternatively: With through-hole With internal thread "With accessories" means indirect mounting via an intermediate element.
Pneumatic connection	M5
Note on materials	RoHS-compliant
Flange screws material	Steel
Cover material	Wrought aluminum alloy, anodized
Piston rod material	High-alloy steel
Cylinder barrel material	Wrought aluminum alloy, smooth-anodized
Operating pressure (psi)	14,500...145,000 psi