




PS*

PISTON TYPE PRESSURE SWITCH SERIES 21

p max 650 bar
max adjustable p 35 - 140 - 350 - 630 bar


OPERATING PRINCIPLE



TECHNICAL CHARACTERISTICS

PRESSURE SWITCH		PS*2	PS*4	PS*6	PS*8
Pressure adjustment range	bar	3 ÷ 35	6 ÷ 140	10 ÷ 350	20 ÷ 630
Max operating pressure	bar	350	350	650	650
Hysteresis	see p. 5				
Repeatability	< ± 1 % of set pressure				
Electrical characteristics	see p. 3				
Ambient temperature range	°C	-20 / +50			
Fluid temperature range	°C	-20 / +80			
Fluid viscosity range	cSt	10 ÷ 400			
Recommended viscosity	cSt	25			
Fluid contamination degree	according to ISO 4406:1999 class 20/18/15				
Mass	kg	0.67			

SYMBOLS



1 - IDENTIFICATION CODE

P S / 21 - K1 / K									
Piston type pressure switch				Adjustment knob					
Mounting type:				Electrical connection:					
P = subplate mounting				for EN 175301-803 (ex DIN 43650) connector					
T = threaded port 1/4" BSP				(included in the supply)					
Pressure adjustment range:				Seals: N = standard NBR seals for mineral oils (standard)					
2 = 3 ÷ 35 bar				V = FPM seals for special fluids					
6 = 10 ÷ 350 bar				Series N.					
4 = 6 ÷ 140 bar				(the overall and mounting dimensions remain unchanged from 20 to 29)					
8 = 20 ÷ 630 bar									

2 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals (code N). For fluids HFDR type (phosphate esters) use FPM seals (code V). For the use of other fluid types such as HFA, HFB, HFC, please consult our technical department. Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics. The fluid must be preserved in its physical and chemical characteristics.


3 - ELECTRICAL CHARACTERISTICS

		AC		DC	
Power supply	V	125	250	30	250
Max load on contacts	A	7	5	5	0.2
- resistive		4	2	3	0.02
Electrical insulation (according to CEI EN 60204)		> 1 M ohm at 500 Vdc			
Max switching rate	switches/min	120			
Protection class (according to CEI EN 60529)		IP65			

4 - INSTALLATION





The pressure switches can be installed in any position without impairing its correct operation. Ensure that there is no air in the hydraulic circuit.

The subplate mounting pressure switch PSP type is fixed by means of screws on a flat surface with planarity and roughness values equal to or better than those indicated in the relative symbols. If the minimum values are not observed, the fluid can easily leak between the valve and the mounting surface.



5 - HYSTERESIS CHARACTERISTICS

(values measured with viscosity of 36 cSt at 50°C)




6 - SUBPLATES FOR STACK MOUNTING


The PSP pressure switches can be stack mounted by means of ISO 4401-03 (CETOP 03 subplates), code 1950611 and 1950621.

The subplate code 1950611 permits the connection between the pressure switch and A and/or B ports, depending on where the bolt (1) is installed. The subplate code 1950621 permits the connection between the pressure switch and the P port.

SUBPLATE CODE 1950611 (A and B ports connection)




SUBPLATE CODE 1950621 (P port connection)



MAX PRESSURE 350 BAR

MOUNTING INTERFACE

ISO 4401-03-02-0-05
(CETOP 4.2-4-03-350)



dimensions in mm

1	Hexagonal head M4x12 bolt with "bonded seal" type 400-002 (Dowty) Unscrew the bolt and its seal from the side where the switch is installed
2	Mounting surface with sealing rings 4 OR type 2037 (9.25x1.78) - 90 Shore

7 - OVERALL AND MOUNTING DIMENSIONS

