

TECHNICAL DATA

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers



Key features

- 6-digit backlight display reads the data clearly
- Signal detection reminder avoids invalid detection actions
- Maximum/minimum/average value and final readings
- Setting/Turning off the automatic power-off function
- Small size and easy to hold
- Easy switching of the contact and non-contact measurement modes
- Different speed measuring heads and rotational speeds adapt to different measurement occasions
- 1-year warranty

Product overview: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

The Fluke 931 tachometer is a handheld tachometer, which integrates the contact and non-contact speed measurement functions and can accurately measure the revolutions per minute (RPM) or surface speed and distance. Fluke 930 is equivalent to a Fluke 931 with minimum configuration. With only the non-contact measuring function provided, it's more affordable and offers consistent quality.



Applications:

- Heavy manufacturing environments, e.g. automotive, textile, pulp and paper, metalwork
- Water purification plants
- Machining and chemical manufacturing plants
- HVAC compressors for industrial systems

Specifications: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

| Rotation speed meas | urement | |
|-----------------------|---|------------------------------------|
| Range | Optical (non-contact) measurement: 1 to 99999 revolutions/minute Contact measurement: 1 to 19999 revolutions/minute (Fluke 931 only) | |
| Precision | ±0.02%RD+1 | |
| Sensing distance | (optical) 500 mm | |
| Specifications | | |
| Specifications | | |
| Battery type | | (2) 1.5V LR6 (alkaline) AA battery |
| Battery life | | About 40 hours |
| Operating temperature | | 0°C to 50°C |
| Storage temperature | | -20°C to 70°C |

| Storage temperature | -20°C to 70°C |
|---------------------|------------------|
| Weight | 250 g |
| Dimensions | 175 × 60 × 28 mm |
| Warranty period | 1 vear |



Ordering information



Fluke 931

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

- 0.1 m wheel
- Conical speed measuring head
- Inner cone speed measuring head
- Lengthening rod
- 10 reflective stripes

FLUKE-931 ESP

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

- 0.1 m wheel
- Conical speed measuring head
- Inner cone speed measuring head
- Lengthening rod
- 10 reflective stripes

Fluke. Keeping your world up and running.®

Fluke Corporation PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2025 Fluke Corporation. Specifications subject to change without notice. 07/2025

Modification of this document is not permitted without written permission from Fluke Corporation