


# Air solenoid valve

## VUVS-L25-M32C-MD-G14-F8-1B2

Part number: 575481



[PDF](#) General operating condition

### Datasheet product reliability

The information in this "Product reliability data sheet" is based on products being used as intended. This includes complying with all specifications in data sheets, catalogues, user documentation and the general operating conditions. The user alone is responsible for determining whether a product is suitable for a particular application.

Feature	Value
Certificate issuing authority	DNVGL-TAA000011J
Relevant basic safety principles <sup>1)</sup>	Yes
Service-life value B <sub>10</sub> <sup>2)</sup>	10 Mio cycles
Service-life value B <sub>10D</sub> <sup>3)</sup>	20 Mio cycles
Relevant well-tried safety principles <sup>4)</sup>	Yes
Fault exclusion	Automatic change of the normal position of the switching element of the main stage without a control signal. The control signal for pilot-controlled solenoid valves consists of the electrical control signal for the valve coil and the pneumatic signal (pilot air supply) of the pilot valve. Bursting of the valve housing: externally directed failure of the material structure with a sudden release of the medium and associated pressure drop (according to ISO 5598, 3.2.85).
Design characteristics	Mechanical spring return
Lap	Overlap
Vibration resistance	Transport application test with severity level 2 in accordance with FN942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27
Max. positive test pulse with 0 signal	2000 µs
Max. negative test pulse with 1 signal	3600 µs

- 1) The product-relevant basic safety principles are fulfilled according to the ISO 13849-2.
- 2) The ascertainment of characteristic service life values is generally based on the ISO 19973 "Pneumatic fluid power - Assessment of component reliability by testing".
- 3) B<sub>10D</sub> value determined on the basis of ISO 13849-1: e.g. B<sub>10D</sub>=2\*B<sub>10</sub>. Whether this value is suitable for a specific application must be checked and confirmed by the user.
- 4) The product-relevant well-tried safety principles are fulfilled according to the ISO 13849-2.