

232.50.100 10000 psi 2nd scale bar 1/2 NPT lower back mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number:	84287888
Quantity:	1 pcs.
Overview:	<p>232.50.100 10000 psi 2nd scale bar 1/2 NPT lower back mount</p> <p>Measuring System 316L</p> <p>Ingress protection: IP 65</p> <p>class 1.0</p> <p>front flange, polished SS</p> <p>Window: laminated safety glass</p> <p>Permissible ambient temperature: -40 ... +60 °C</p> <p>Permissible medium temperature: + 200 °C</p> <p>Pressure Gauge Standard: International (standard Europe)</p> <p>2nd scale red</p> <p>*WIKA*</p> <p>with Serial number</p> <p>with QR Code</p> <p>individual text for dial: *Made in*</p> <p>Label: WIKA standard without / with Tag-number</p>
Details:	<p>Bourdon Tube Pressure Gauges, Stainless Steel</p> <p>Series</p> <p>Model: 232.50</p> <p>Specifications according to data sheet: PM 02.02</p> <p>Measuring system: stainless steel</p> <p>Case filling: without</p> <p>Nominal size: 100 mm</p> <p>Scale range: 0...10000 psi</p> <p>2nd Scale or Special Scale: 2nd scale bar</p> <p>Process connection: 1/2 NPT</p> <p>Connector location: lower back mount</p> <p>Mounting flange/bracket: front flange, polished SS</p> <p>Window: laminated safety glass</p> <p>Pointer: standard pointer</p> <p>Accuracy class: class 1.0</p> <p>Material pressure element: Measuring System 316L</p> <p>Ingress protection: IP 65</p> <p>Permissible medium temperature: + 200 °C</p> <p>Permissible ambient temperature: -40 ... +60 °C</p> <p>Pressure Gauge Standard: International (standard Europe)</p> <p>color for 2.scale (inside): red RAL 3020</p> <p>Manufacturer logo: *WIKA*</p> <p>with Serial number</p> <p>QR code with extended serial number on dial</p> <p>individual text for dial: *Made in*</p>