

# UltraSoniX™

Glycerin-FREE  
Ultrasonic Couplant

**UltraSoniX** is a glycerin-free ultrasonic couplant that is compatible with most materials, has excellent ferrous corrosion inhibition and does not contain formaldehyde or glycol ether.

## PRODUCT DESCRIPTION

Remains in place on vertical and overhead surfaces. Medium viscosity couplant ideal for spreading.

Meets FAA Advisory Circular issued 9/20/2013 AC 25-29 which states: Procedures need to ensure glycerin is not used on aluminum materials, as it may cause corrosion.

No glycerin as required for carbon fiber composites.

Water-soluble. Easy to remove.

Environment and operator friendly.

**REMOVAL:** Wipe with a rag or water wash.



## PRODUCT SPECIFICATIONS

**Operating Range:**  
10° to 220° F (-12° to 104° C)

- **Viscosity:** Medium flowable gel
- **Halogens & Sulfur:** Less than 50 ppm
- **pH:** 8.0 nominal at 20° C
- **Compliance:**  
ASTM F519  
ASME Boiler & Pressure Vessel Code (T-533)  
NAVSHIPS 250-1500  
FAA-AC #25-29 (Glycerin-free)  
Nuclear Grade (< 50 ppm Halogens & Sulfur)

## PACKAGING

Carton of (12) 4-oz / 118 ml bottles  
Carton of (12) 8-oz / 236.6 ml bottles  
Carton of (12) 12-oz / 355 ml bottles  
1 gallon / 3.8 liter cubitainer  
5 gallon / 19 liter cubitainer  
55 gallon / 208 liter drum

SDS available at: [echoultrasonics.com](http://echoultrasonics.com)



Echo Ultrasonics®, LLC  
774 Marine Drive | Bellingham, WA 98225  
[echoultrasonics.com](http://echoultrasonics.com) | [sales@echoultrasonics.com](mailto:sales@echoultrasonics.com)  
360.671.9121